
Product information from SMART Identify labelling machines.











Ring 412MA Smart series

<u>Feature</u>

- Automatic Labelling / Side Apply
- High Performance , Reliable and durable
- Ridged Steel Cabinet with media Window
- Easy to loading the roll rabel.
- High resolution 300 Dpi
- light, high speed processing by 32Bit Risc CPU 8 MB SDRAM&4MB flash memory
- Print Method Transfer& Direct thermal
- Roll label ID core 3" OD max 8" Face out
- Print width 4"
- Stroke length: 150 mm
- Labeling position tolerance : +- 1-2 mm
- RS232/USB Interface
- Weight: 50 Kgs (Approx)

Prefeed Belt Conveyor

- Structure : Aluminium Profile
- Low friction flat type
- Speed 0-15 m/min adjustable
- 90 watts Oriental motor 220VAC
- Side guide adjustable

This system was designed for print & apply on the packaging with a label to be placed in a specific position.

The products are coming to the system in reached position and are keep moving in the PVC belt conveyor system. A sensor is detecting the reference point on the product so the label

- LCD Display 2 lines by 16 characters Black can be apply according to this point.

The RING 412MA printer with integrated Air jet Cylinder type controlled by built in an Advanced control unit, is applying the label.

quick change the set up time.

The system can work with small and large product.

The system consist of

- Printer & Applicator 412 MA Made in JAPAN
- Prefeed PVC belt conveyor
- Structure and Floor stand with adjustment
- Product sensor
- With Bartender latest version



Smart Identify Ltd. 594/9 Hathairat Rd. Bangchan Klongsawa Bangkok 10510 THAILAND www.smartiden.com