



**LABELING & MARKING**

**SERIES**

**DYNAMIC**



<i>Labeler</i> Etichettatrice	<i>Max label reel diameter</i> Diametro max rotolo etichette	<i>Max speed</i> Velocità max	<i>Max frequency</i> Frequenza max	<i>Accuracy</i> Precisione di erogazione
DYNAMIC 110	280mm - 11.02"	up to 40 m/min - 131 ft/min	680 pcs/min	± 1,1mm ± 0.043"
DYNAMIC 160	280/300mm <sup>1</sup> - 11,02"/11.81"	up to 40 m/min - 131 ft/min	680 pcs/min	± 1,1mm ± 0.043"

<sup>1</sup> The maximum diameter 280mm can be raised to 300mm where the roll width is significantly less than the maximum allowed



**LABELING & MARKING**

***A small champion of efficiency and effectiveness. Ensures excellent performance and functionality of more advanced labeling machines***

*Very small dimensions, total modularity and a respectable speed, they allow an easy integration into any production line, also with constantly variable speed. It can be equipped with various devices for printing and marking; and with all the most important accessories*

**Un piccolo campione di efficienza e di efficacia. Assicura ottime prestazioni e le funzionalità delle etichettatrici più avanzate**

Dimensioni ridottissime, totale modularità e una velocità di tutto rispetto, ne consentono un'agevole integrazione in qualsiasi linea produttiva, anche con velocità costantemente variabile.

È equipaggiabile con diversi dispositivi per la stampa e la marcatura; e con tutti gli accessori più importanti

# DYNAMIC FACTS



## LABELING & MARKING

<b>CHANGE ON THE FLY</b> 	<b>PW SET UP</b> 	<b>MAX SPEED</b> 40m/min 	<b>FREQUENCY</b> 680pcs/min 	<b>+</b>
<b>OFF LINE</b> 	<b>JOG</b> 	<b>LABELING PROGRAMS</b> 	<b>ELECTRONIC TARGET</b> 	<b>ABSOLUTE TARGET</b> 
<b>1:1</b> 	<b>PRE ALARM*</b> 	<b>280/300</b> 		
<b>COUNTER</b> 	<b>SYNCROSPEED</b> 			
<b>FREQUENCY CHECK</b> 	<b>SAFE DETECTION</b> 	<b>MISSING LABEL RECOVERY</b> 	<b>AUTOMATIC STOP</b> 	
<b>ELECTRICAL SIGNALS</b> 				
<b>T.T. (on moving)</b> 	<b>TIJ (on moving)</b> 			

High end / Low end

**+** Additional functionality compared to the lower model (Easy) in the range  
 Funzionalità aggiuntive rispetto al modello inferiore (Easy) nella gamma

\* Optional  
 \* Optional

