


iX4L Industrial Barcode Printer

- Color display screen for visualized operation
- Complete components bring various combination



Model	IX4L
Printing Method	Thermal transfer, Direct thermal
Resolution	203 dpi / 6 ips
Max. Printing Speed	Optional 300 dpi / 6 ips
Max. Printing Length	2286 mm (203 dpi) 1524 mm (300 dpi)
Max. Printing Width	104 mm
Protocol	DPL, ZPL-II, EPL
Media Type	Continuous Paper, Gap, Black mark Sensor, Punched Hole Label, ECO Thermal Labels, Coated Semi-gloss Art Label, Synthetic Paper Label, Vinyl, Textile ribbon
Media Core Diameter	1.5"/3"(ID.); Max. 10"(OD.)
Media Thickness	60 um ~ 250 um
Media Width	25 mm ~ 120 mm
Ribbon Type	Wax, Wax/Resin, Resin
Ribbon Core Diameter	1 inch
Ribbon Width	30 mm ~ 110 mm
Ribbon Length	450 meters
Sensor	Paper out detect, Ribbon out detect, Print head left detect, Print head temperature detect Power Temp Detection, Motor Temp Detection
Standard Interfaces	USB Type B ×1, USB HOST ×1, RJ45 ×1, RS232(9-pin) ×1
Optional Interfaces	WiFi
RAM	32 MB
Flash	128 MB
Display	3.5 inch Colour Display
Optional&Accessory	Peeler Module , Cutter Module , External Label Roll Holder
Dimension (L*W*H)	460.4 x 263.6 x 330.5 mm
Weight	12.0 KG
Agency Approval	CE, FCC, CCC, BIS,CB, UL, RoHS, WEEE



Smart Identify Ltd.

38 Soi Sanwa 31, Bangchan, Klong Samwa,
Bangkok 10510 Thailand

www.smartiden.com

[smartiden.com](https://www.facebook.com/smartiden.com)

[@smartiden.com](https://www.linkedin.com/company/smartiden.com)